

# Outdoor Type 3R/4 Side Mount Cooling Units

**Electronics are the lifeblood of your operation.**

Keep them properly cooled and consistently operating with proper thermal management.



Btu/h	2000 - 3000	3000 - 4000	5000 - 7000	7000 - 8500	9000 - 12000	12000 - 14000	16000 - 18000	20000 - 24000
Available Volts	115	115 / 460 1Ø	115 / 400 / 460 3Ø	115 / 400 / 460 3Ø	115 / 400 / 460 3Ø	400 / 460 3Ø	400 / 460 3Ø	400 / 460 3Ø
Height (in)	20.2	29.3	36	47.6	53	59.1	59.1	65.6
Width (in)	10.1	15.6	12	15.6	16	15.9	19	19
Depth (in)	10.8	11.6	12	12.8	11.9	18.4	21	24.5

Part #	UPC Code	Voltage
AB-SAC115V3000NF	70735365359	115
AB-SAC115V4000NF	70735365360	115
AB-SAC460V4000NF	70735365361	460
AB-SAC115V7000NF	70735365362	115
AB-SAC460V7000NF	70735365363	460
AB-SAC115V8500NF	70735365364	115
AB-SAC460V8500NF	70735365365	460
AB-SAC115V12000NF	70735365366	115
AB-SAC460V12000NF	70735365367	460
AB-SAC460V14000NF	70735365368	400/460 (3Ø)
AB-SAC460V18000NF	70735365369	400/460 (3Ø)
AB-SAC460V24000NF	70735365370	400/460 (3Ø)

Wide condenser fin spacing, rugged, long lasting backward curved impeller fans, proper long internal air paths, and hermetically sealed refrigeration circuits coupled with filter kit, corrosion-resistant and voltage options make these outdoor Type 3R/4 side mount cooling units reliable and relatively maintenance-free.

230 volt models & RAL 7035 available upon request.

