

# Washdown 4/4X Side Mount Cooling Units

**Electronics are the lifeblood of your operation.**

Keep them properly cooled and consistently operating with proper thermal management.



Btu/h	2000 - 3000	3000 - 4000	5000 - 7000	7000 - 8500	9000 - 12000	12000 - 14000	16000 - 18000	20000 - 24000
Available Volts	115	115 / 460 1Ø	115 / 400 / 460 3Ø	115 / 400 / 460 3Ø	115 / 400 / 460 3Ø	400 / 460 3Ø	400 / 460 3Ø	400 / 460 3Ø
Height (in)	20.2	29.3	36	47.6	53	59.1	59.1	65.6
Width (in)	10.1	15.6	12	15.6	16	15.9	19	19
Depth (in)	10.8	11.6	12	12.8	11.9	18.4	21	24.5

Part #	UPC Code	Voltage
AB-SAC115V3000NFX	70735365371	115
AB-SAC115V4000NFX	70735365372	115
AB-SAC460V4000NFX	70735365373	460
AB-SAC115V7000NFX	70735365374	115
AB-SAC460V7000NFX	70735365375	460
AB-SAC115V8500NFX	70735365376	115
AB-SAC460V8500NFX	70735365377	460
AB-SAC115V12000NFX	70735365378	115
AB-SAC460V12000NFX	70735365379	460
AB-SAC460V14000NFX	70735365380	400/460 (3Ø)
AB-SAC460V18000NFX	70735365381	400/460 (3Ø)
AB-SAC460V24000NFX	70735365382	400/460 (3Ø)

Wide condenser fin spacing, rugged, long lasting backward curved impeller fans, proper long internal air paths, and hermetically sealed refrigeration circuits coupled with filter kit, corrosion-resistant and voltage options make these washdown 4/4X side mount cooling units reliable and relatively maintenance-free.

230 volt models &  
316 Stainless Steel  
available upon request.

